

View Online at <https://aerobasegroup.com/nsn/5910-01-366-0815>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Not established

**Terminal Length:**

16.0 millimeters

**Body Diameter:**

5.5 millimeters

**Body Length:**

16.5 millimeters

**Center To Center Distance Between Terminals Parallel To Diameter:**

5.0 millimeters

**Terminal Diameter:**

0.5 millimeters

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Electrical Polarization:**

Polarized

**End Application:**

6625-01-285-9218 generator, signal

**Capacitance Value Per Section:**

10.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 105.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

63.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

0.100

**Equivalent Series Resistance At Reference Temperature In Ohms:**

16.60

**Dc Leakage At Reference Temp:**

6.300 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0