

View Online at https://aerobasegroup.com/nsn/5910-01-366-3527

| Body Style: | |
|------------------------|--|
| Chip type | |
| Reliability Indicato | Dr: |
| Not established | |
| Body Length: | |
| 0.055 inches | |
| Body Width: | |
| 0.055 inches | |
| Body Height: | |
| Between 0.020 inch | nes and 0.057 inches |
| Schematic Diagram | m Designator: |
| No common or grou | unded electrode (s) |
| Capacitance Value | e Per Section: |
| 18.000 picofarads s | single section |
| Nonderated Opera | ating Temp: |
| Between -55.0 degr | rees celsius and 125.0 degrees celsius |
| Nonderated Contin | nuous Voltage Rating And Type Per Section: |
| 50.0 dc single section | on |
| Tolerance Range F | Per Section: |
| -5.00/+5.00 percent | t single section |
| Special Features: | |
| Additional low volta | ge humidity test |
| Test Data Docume | ent: |
| 97942-587r222 drav | wing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specif | fication, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And | d Quantity: |
| 2 bonding pad | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A010b0 | |