NSN 5910-01-366-7389

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-366-7389

| Body Style: |
|--|
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Length: |
| 0.420 inches |
| Body Width: |
| 0.170 inches |
| Body Height: |
| 0.290 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.010 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section |
| |
| 100.0 dc single section |
| 100.0 dc single section Tolerance Range Per Section: |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity: |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity: 2 uninsulated wire lead |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a |
| 100.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a |
| Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: |
| Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: |