

View Online at <https://aerobasegroup.com/nsn/5910-01-367-2726>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Terminal Length:

31.8 millimeters

Body Length:

Between 4.6 millimeters and 5.1 millimeters

Body Width:

Between 4.6 millimeters and 5.1 millimeters

Body Height:

Between 2.0 millimeters and 2.5 millimeters

Center To Center Distance Between Terminals Parallel To Length:

Between 4.7 millimeters and 5.5 millimeters

Terminal Diameter:

Between 0.6 millimeters and 0.7 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

75.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0