NSN 5910-01-367-6108



Ceramic Dielectric Fixed Capacitor - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5910-01-367-6108 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 1.000 **Terminal Length:** 1.250 inches **Body Diameter:** Between 0.130 inches and 0.150 inches **Body Length:** Between 0.380 inches and 0.400 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Section Quantity: Capacitance Value Per Section:** 470.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 ribbon **Specification Data:** 81349-mil-c-55681/5 government specification Shelf Life: N/a **Unit Of Measure:**

No Fiig:

A010b0

Mil-std (military Standard):

Mil-c-20 spec.

Demilitarization: