## NSN 5910-01-367-7894

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-367-7894

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Established

**Terminal Length:** 

1.250 inches

**Body Length:** 

Between 0.180 inches and 0.200 inches

**Body Width:** 

Between 0.180 inches and 0.200 inches

**Body Height:** 

Between 0.080 inches and 0.100 inches

**Terminal Diameter:** 

Between 0.023 inches and 0.029 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**End Application:** 

1430-01-087-6330 radar set, semi-trailer mounted

**Capacitance Value Per Section:** 

300.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-30.0/+30.0 single section

**Tolerance Range Per Section:** 

-1.00/+1.00 percent single section

**Case Material:** 

Plastic

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-20 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

**Specification Data:** 

81349-mil-c-20/35 government specification

Shelf Life:

N/a

## NSN 5910-01-367-7894

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A010b0