NSN 5910-01-367-9837

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-367-9837

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Length:
0.650 inches
Body Width:
0.240 inches
Body Height:
0.360 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.470 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section
100.0 dc single section
100.0 dc single section Tolerance Range Per Section:
100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal
100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent:
100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000
100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment:
100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder
100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: