

View Online at https://aerobasegroup.com/nsn/5910-01-368-1098

Body Style:
Chip type
Reliability Indicator:
Established
Body Length:
Between 0.090 inches and 0.130 inches
Body Width:
Between 0.090 inches and 0.130 inches
Body Height:
Between 0.030 inches and 0.102 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
8.200 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
90.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Tolerance Range Per Section:
-0.25/+0.25 percent single section
Case Material:
Ceramic
Terminal Surface Treatment:
Palladium and silver
Precious Material And Location:
Terminal surfaces palladium and terminal surfaces silver
Test Data Document:
81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificati
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 bonding pad
Specification Data:
81349-mil-c-55681/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5910-01-368-1098 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

Fiig: A010b0

