NSN 5910-01-368-7328

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



segroup com/psp/5010-01-368-7328

View Online at https://aerobasegroup.com/nsn/5910-01-368-7328
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
1.625 inches
Body Diameter:
Between 0.500 inches and 0.520 inches
Body Length:
Between 1.345 inches and 1.405 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.180 microfarads single section
Nonderated Operating Temp:
Between -65.0 degrees celsius and 100.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Metal
Dissipation Factor At Reference Tempurature In Percent:
0.150
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic
Case Insulation Material:
Plastic
Test Data Document:
83149-mil-c-83421 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:

2 uninsulated wire lead **Specification Data:**

81349-mil-c-83421/1 government specification

Shelf Life:

N/a

NSN 5910-01-368-7328

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0