NSN 5910-01-369-7514

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-369-7514
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
1.250 inches
Body Length:
0.290 inches
Body Width:
0.290 inches
Body Height:
0.090 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
620.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Ceramic
Dissipation Factor At Reference Tempurature In Percent:
0.150
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Specification Data:
81349-mil-c-20/36 government specification

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5910-01-369-7514

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0