

View Online at <https://aerobasegroup.com/nsn/5910-01-369-7515>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

2.250 inches

Body Diameter:

0.281 inches

Body Length:

0.641 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Electrical Polarization:

Polarized

Capacitance Value Per Section:

27.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

24.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

125.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

7.200

Dc Leakage At Reference Temp:

5.000 microamperes

Test Data Document:

81349-mil-c-39006 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-39006/25 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0