

View Online at https://aerobasegroup.com/nsn/5910-01-372-4044

Body Style:	
Dual inline	
Reliability Indicat	Dr:
Established	
Reliability Failure	Rate Level In Percent:
0.010	
Terminal Length:	
0.148 inches	
Body Length:	
0.092 inches	
Body Width:	
0.260 inches	
Body Height:	
0.128 inches	
Schematic Diagra	m Designator:
No common or gro	unded electrode (s)
Capacitance Valu	e Per Section:
100000.000 picofa	ads single section
Voltage Tempura	ure Limits Per Section In Percent Capacitance Change:
-25.0/+15.0 with ra	ed voltage applied single section
Nonderated Oper	ating Temp:
Between -55.0 deg	rees celsius and 125.0 degrees celsius
Nonderated Cont	nuous Voltage Rating And Type Per Section:
50.0 dc single sect	on
Tolerance Range	Per Section:
-20.00/+20.00 perc	ent single section
Case Material:	
Ceramic	
Insulation Resista	nce At Reference Temp:
100000.0 megohm	8
Dissipation Facto	r At Reference Tempurature In Percent:
2.500	
Terminal Surface	Treatment:
Solder	
Test Data Docum	ent:
81349-mil-c-39014	specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes of	ommercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and	performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type Ar	d Quantity:
2 tab, solder lug	
Specification Dat	
-	22 government specification
Shelf Life:	
N/a	



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0