## NSN 5910-01-373-5426

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-373-5426

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.400 inches
Body Width:
0.120 inches
Body Height:
0.200 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.018 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
Tolerance Range Per Section: -5.00/+5.00 percent single section
-5.00/+5.00 percent single section
-5.00/+5.00 percent single section  Case Material:
-5.00/+5.00 percent single section  Case Material:  Metal
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp:
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp:  10000.0 megohms
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp:  10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp:  10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  1.000
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.000  Case Insulation Material:
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp:  10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  1.000  Case Insulation Material:  Plastic
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.000  Case Insulation Material:  Plastic  Terminal Type And Quantity:
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.000  Case Insulation Material:  Plastic  Terminal Type And Quantity: 2 uninsulated wire lead
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp:  10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  1.000  Case Insulation Material:  Plastic  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.000  Case Insulation Material:  Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.000  Case Insulation Material:  Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.000  Case Insulation Material:  Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:
-5.00/+5.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.000  Case Insulation Material:  Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: