NSN 5910-01-373-6938

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-373-6938

| Body Style: |
|---|
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Length: |
| 0.400 inches |
| Body Width: |
| 0.100 inches |
| Body Height: |
| 0.200 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.320 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -1.00/+1.00 percent single section |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 10000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.000 |
| Case Insulation Material: |
| Plastic |
| |
| Terminal Type And Quantity: |
| Terminal Type And Quantity: 2 uninsulated wire lead |
| |
| 2 uninsulated wire lead |
| 2 uninsulated wire lead Shelf Life: |
| 2 uninsulated wire lead Shelf Life: N/a |
| 2 uninsulated wire lead Shelf Life: N/a |
| 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: |
| 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: |