NSN 5910-01-373-8230 Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-373-8230         |  |
|---|--|
| Body Style:   |  |
| Chip type   |  |
| Reliability Indicator:  |  |
| Not established   |  |
| Terminal Length:  |  |
| 0.020 inches  |  |
| Body Length:  |  |
| 0.079 inches  |  |
| Body Width:   |  |
| 0.049 inches  |  |
| Body Height:  |  |
| 0.051 inches  |  |
| Schematic Diagram Designator:   |  |
| No common or grounded electrode (s)                                   |  |
| Insulation Resistance At Maximum Operating Temp:                      |  |
| 10000.0 megohms   |  |
| Capacitance Value Per Section:  |  |
| 33000.000 picofarads single section                                   |  |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |  |
| -15.0/+15.0 with rated voltage applied single section                 |  |
| Nonderated Operating Temp:  |  |
| Between -55.0 degrees celsius and 125.0 degrees celsius               |  |
| Nonderated Continuous Voltage Rating And Type Per Section:            |  |
| 50.0 dc single section  |  |
| Tolerance Range Per Section:  |  |
| -5.00/+5.00 percent single section                                    |  |
| Case Material:  |  |
| Ceramic   |  |
| Insulation Resistance At Reference Temp:                              |  |
| 100000.0 megohms  |  |
| Dissipation Factor At Reference Tempurature In Percent:               |  |
| 0.100   |  |
| Terminal Surface Treatment:   |  |
| Silver and nickel   |  |
| Precious Material And Location:                                       |  |
| Plated terminals silver   |  |
| Terminal Type And Quantity:   |  |
| 2 bonding pad   |  |
| Shelf Life:   |  |
| N/a   |  |
| Unit Of Maggura   |  |

## NSN 5910-01-373-8230

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0