## NSN 5910-01-373-9724

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-373-9724 **Body Style:** W/o mtg facilities, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** 0.984 inches **Body Diameter:** 0.315 inches **Body Length:** 0.453 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.135 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms: Electrical Polarization:** Polarized **Capacitance Value Per Section:** 100.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 0.170 Dc Leakage At Reference Temp: 0.400 microamperes **Terminal Surface Treatment:** 

Solder **Case Insulation Material: Plastic** 

## NSN 5910-01-373-9724

Electrolytic Fixed Capacitor - Page 2 of 2



	Ī	erminal	Type	And	Quantit	y:
--	---	---------	------	-----	---------	----

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0