Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-373-9726

#### **Body Style:**

W/o mtg facilities, terminal (s) on one end

## **Reliability Indicator:**

Not established

## **Terminal Length:**

0.984 inches

#### **Body Diameter:**

0.236 inches

#### **Body Length:**

0.300 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

0.120 inches

#### **Terminal Diameter:**

0.020 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Anode Type:

Plain foil

## Impedance At Minimum Operating Tempurature In Ohms:

4.0

## **Electrical Polarization:**

Polarized

### Capacitance Value Per Section:

15.000 microfarads single section

### Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### Case Material:

Metal

### **Capacitive Electrode Material:**

Aluminum

### **Dissipation Factor At Reference Tempurature In Percent:**

0.140

### Dc Leakage At Reference Temp:

0.400 microamperes

## **Terminal Surface Treatment:**

Solder

## **Case Insulation Material:**

Plastic

Electrolytic Fixed Capacitor - Page 2 of 2



# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0