Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-374-5954

## Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

1.000

## **Terminal Length:**

1.250 inches

**Body Length:** 

0.190 inches

Body Width:

0.190 inches

Body Height:

0.090 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Capacitance Value Per Section:

91.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

## **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### Case Material:

Ceramic

**Terminal Surface Treatment:** 

Solder

## Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-20/35 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

--

Demilitarization:

No

# NSN 5910-01-374-5954

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

