NSN 5910-01-377-5258

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-377-5258

Body Style: W/o mtg facilities, axial terminals **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.001 **Terminal Length:** 1.625 inches **Body Diameter:** Between 0.660 inches and 0.690 inches **Body Length:** 2.075 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 10.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 300000.0 megohm-microfarads **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic **Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-87217 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead

81349-mil-c-87217/01 government specification

Specification Data:

NSN 5910-01-377-5258

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0