## NSN 5910-01-377-7507

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



Body Style: Chip type Reliability Indicator: Not established Terminal Length: 0.015 inches Body Length: 0.110 inches Body Width: 0.110 inches Body Height: Between 0.030 inches and 0.102 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section Tolerance Range Per Section:
Reliability Indicator: Not established Terminal Length: 0.015 inches Body Length: 0.110 inches Body Width: 0.110 inches Body Width: 0.110 inches Body Height: Between 0.030 inches and 0.102 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section
Terminal Length:  0.015 inches  Body Length:  0.110 inches  Body Width:  0.110 inches  Body Height:  Between 0.030 inches and 0.102 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
Terminal Length:  0.015 inches  Body Length:  0.110 inches  Body Width:  0.110 inches  Body Height:  Between 0.030 inches and 0.102 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
0.015 inches  Body Length: 0.110 inches  Body Width: 0.110 inches  Body Height:  Between 0.030 inches and 0.102 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section: 2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section
Body Length: 0.110 inches Body Width: 0.110 inches Body Height: Between 0.030 inches and 0.102 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 2.700 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section
0.110 inches  Body Width: 0.110 inches  Body Height:  Between 0.030 inches and 0.102 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section: 2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section
Body Width:  0.110 inches  Body Height:  Between 0.030 inches and 0.102 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
O.110 inches  Body Height:  Between 0.030 inches and 0.102 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
Body Height:  Between 0.030 inches and 0.102 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
Between 0.030 inches and 0.102 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
No common or grounded electrode (s)  Capacitance Value Per Section:  2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
Capacitance Value Per Section:  2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
2.700 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
Between -55.0 degrees celsius and 125.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -70.0/+110.0 single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section
90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section
Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section
500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -70.0/+110.0 single section
-70.0/+110.0 single section
Tolerance Range Per Section:
-0.25/+0.25 picofarads single section
Case Material:
Ceramic
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 bonding pad
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0