NSN 5910-01-377-9956

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-377-9956

| Body Style: |
|--|
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 6.0 millimeters |
| Body Length: |
| 10.0 millimeters |
| Body Width: |
| 8.5 millimeters |
| Body Height: |
| 3.0 millimeters |
| Terminal Diameter: |
| 0.5 millimeters |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.010 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 100.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| Mondoratod Continuodo Voltago Mating Ana Typo i or Cootion. |
| 250.0 dc single section |
| |
| 250.0 dc single section |
| 250.0 dc single section Tolerance Range Per Section: |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: |
| 250.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: |