## NSN 5910-01-380-8826

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-380-8826
Body Style:
Chip type
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Body Length:
0.080 inches
Body Width:
0.050 inches
Body Height:
Between 0.020 inches and 0.055 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
47.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Detween -33.0 degrees ceisius and 123.0 degrees ceisius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Terminal Type And Quantity:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Terminal Type And Quantity:  2 bonding pad
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Terminal Type And Quantity:  2 bonding pad  Shelf Life:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a  Unit Of Measure:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: