## NSN 5910-01-381-7711

**Body Style:** 

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-381-7711

W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 1.000 **Terminal Length:** 1.250 inches **Body Length:** 0.190 inches **Body Width:** 0.200 inches **Body Height:** 0.090 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 35000.0 megohms **Capacitance Value Per Section:** 0.082 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 200000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 1.000 **Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data: 81349-mil-c-55514/8 government specification

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-381-7711

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0