

View Online at https://aerobasegroup.com/nsn/5910-01-381-8700

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

### **Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:** 

1.000

#### **Terminal Length:**

1.250 inches

**Body Length:** 

0.190 inches

#### **Body Width:**

0.190 inches

#### **Body Height:**

0.090 inches

#### Center To Center Distance Between Terminals Parallel To Length:

# 0.200 inches

**Terminal Diameter:** 

0.023 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

## Capacitance Value Per Section:

3.300 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-0.25/+0.25 picofarads single section

#### **Case Material:**

Plastic

# Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-20/35 government specification

# Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A010b0