NSN 5910-01-385-1595

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-385-1595

Body Style:					
W/o mtg facilities, axial terminals					
Reliability Indicator:					
Not established					
Terminal Length:					
1.625 inches					
Body Diameter:					
0.200 inches					
Body Length:					
0.687 inches					
Terminal Diameter:					
0.040 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Features Provided:					
Hermetically sealed case					
Insulation Resistance At Maximum Operating Temp:					
300000.0 megohms					
Capacitance Value Per Section:					
0.068 microfarads single section					
Nonderated Operating Temp:					
Between -65.0 degrees celsius and 100.0 degrees celsius					
Nonderated Continuous Voltage Rating And Type Per Section:					
Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section					
30.0 dc single section					
30.0 dc single section Tolerance Range Per Section:					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material:					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp:					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 3000000.0 megohms					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 3000000.0 megohms Dissipation Factor At Reference Tempurature In Percent:					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 3000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 3000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment:					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 3000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment: Solder					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 3000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment: Solder Dielectric Material:					
30.0 dc single section Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 3000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment: Solder Dielectric Material: Plastic					
Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 3000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment: Solder Dielectric Material: Plastic Case Insulation Material:					
Tolerance Range Per Section: -0.25/+0.25 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 3000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment: Solder Dielectric Material: Plastic Case Insulation Material: Plastic					

N/a

NSN 5910-01-385-1595

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0