## NSN 5910-01-385-4588

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-385-4588

3 F
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.750 inches
Body Diameter:
0.563 inches
Body Length:
Between 1.719 inches and 1.815 inches
Terminal Diameter:
Between 0.025 inches and 0.035 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
1000.0 megohm-microfarads
Capacitance Value Per Section:
1.500 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
25000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.000
Reference Tempurature At Which Rated:
25.0 degrees celsius
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polyester
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:

N/a

## NSN 5910-01-385-4588

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0