

View Online at <https://aerobasegroup.com/nsn/5910-01-385-4591>

**Body Style:**

Chip type

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.100

**Terminal Length:**

Between 0.025 inches and 0.035 inches

**Body Length:**

Between 0.085 inches and 0.115 inches

**Body Width:**

Between 0.035 inches and 0.065 inches

**Body Height:**

Between 0.035 inches and 0.065 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

0.100 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

12.000 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.000

**Dc Leakage At Reference Temp:**

1.000 microamperes

**Reference Temperature At Which Rated:**

25.0 degrees celsius

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 bonding pad

**Specification Data:**

81349-mil-c-55365 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0