

View Online at <https://aerobasegroup.com/nsn/5910-01-386-5841>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.100

Body Diameter:

Between 0.100 inches and 0.200 inches

Body Length:

Between 0.350 inches and 0.450 inches

Terminal Diameter:

0.020 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

700.0 megohm-microfarads

Capacitance Value Per Section:

0.047 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-2.00/+2.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

0.300

Reference Temperature At Which Rated:

25.0 degrees celsius

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polycarbonate

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-55514 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0