

View Online at <https://aerobasegroup.com/nsn/5910-01-386-9539>

Body Style:

Chip type

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

Between 0.083 inches and 0.091 inches

Body Length:

Between 0.130 inches and 0.146 inches

Body Width:

0.083 inches

Body Height:

Between 0.102 inches and 0.118 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.019 inches and 0.043 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Polarized

Capacitance Value Per Section:

3.300 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

6.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

6.000

Equivalent Series Resistance At Reference Temperature In Ohms:

5.000

Dc Leakage At Reference Temp:

0.500 microamperes

Terminal Type And Quantity:

2 bonding pad

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0