

View Online at <https://aerobasegroup.com/nsn/5910-01-388-3735>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

Between 0.177 inches and 0.197 inches

Body Length:

0.359 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

5000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-90.0/+22.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.164 inches

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Dissipation Factor At Reference Temperature In Percent:

3.500

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

1 solder stud and 1 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0