

View Online at <https://aerobasegroup.com/nsn/5910-01-388-5929>

**Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 12.0 millimeters and 20.0 millimeters

**Body Diameter:**

8.5 millimeters

**Body Length:**

13.5 millimeters

**Center To Center Distance Between Terminals Parallel To Length:**

Between 4.0 millimeters and 6.0 millimeters

**Terminal Diameter:**

Between 0.45 millimeters and 0.55 millimeters

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

33.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

25.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

8.000

**Case Insulation Material:**

Rubber

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0