

View Online at https://aerobasegroup.com/nsn/5910-01-388-6898

Body Style:	
Chip type	
Reliability Indicator:	
Established	
Reliability Failure Ra	ate Level In Percent:
0.001	
Body Length:	
0.125 inches	
Body Width:	
0.062 inches	
Body Height:	
0.051 inches	
Schematic Diagram	Designator:
No common or ground	ded electrode (s)
Capacitance Value F	Per Section:
120.000 picofarads si	ngle section
Nonderated Operation	ng Temp:
Between -55.0 degree	es celsius and 125.0 degrees celsius
Tempurature Coeffic	cient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section	
Nonderated Continu	ious Voltage Rating And Type Per Section:
100.0 dc single sectio	n
Tolerance Of Tempu	rature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single sed	ction
Tolerance Range Pe	r Section:
-2.00/+2.00 percent s	ingle section
Case Material:	
Ceramic	
Precious Material Ar	nd Location:
Terminal surfaces pal	lladium and terminal surfaces silver
Test Data Document	t:
81349-mil-c-55681 sp	pecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes com	nmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and pe	erformance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And (Quantity:
2 bonding pad	
Specification Data:	
81349-mil-c-55681/8	government specification
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 5910-01-388-6898 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

Fiig: A010b0

