

View Online at https://aerobasegroup.com/nsn/5910-01-389-8682

| Body Style:  |
|--|
| Chip type  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 1.000  |
| Body Length:   |
| 0.055 inches   |
| Body Width:  |
| 0.055 inches   |
| Body Height:   |
| Between 0.020 inches and 0.057 inches  |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Capacitance Value Per Section:   |
| 0.400 picofarads single section  |
| Nonderated Operating Temp:   |
| Between -55.0 degrees celsius and 125.0 degrees celsius  |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:   |
| 0.0 single section   |
| Nonderated Continuous Voltage Rating And Type Per Section:   |
| 50.0 dc single section   |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:   |
| -30.0/+30.0 single section   |
| Tolerance Range Per Section:   |
| -0.10/+0.10 picofarads single section  |
| Case Material:   |
| Ceramic  |
| Terminal Surface Treatment:  |
| Silver   |
| Precious Material And Location:  |
| Terminals silver   |
| Test Data Document:  |
| 81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 2 bonding pad  |
| Specification Data:  |
| 81349-mil-c-55681/4 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

---



Demilitarization:

No

Fiig:

A010b0