NSN 5910-01-391-2530

Electrolytic Fixed Capacitor - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5910-01-591-2550 |
|---|
| Body Style: |
| W/o mtg facilities, terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.281 inches |
| Mounting Slot Width: |
| 0.062 inches |
| Body Length: |
| 0.875 inches |
| Body Width: |
| 0.875 inches |
| Body Height: |
| 1.625 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.625 inches |
| Terminal Height From Body: |
| 0.281 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Electrical Polarization: |
| Polarized |
| Mounting Facility Type And Quantity: |
| 2 mounting slots |
| Capacitance Value Per Section: |
| 2200.000 microfarads single section |
| Nonderated Operating Temp: |
| Between 55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 15.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Tantalum |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5910-01-391-2530

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0