

View Online at <https://aerobasegroup.com/nsn/5910-01-391-5009>

Body Style:

Chip type

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

Between 0.010 inches and 0.030 inches

Body Length:

Between 0.065 inches and 0.095 inches

Body Width:

Between 0.035 inches and 0.065 inches

Body Height:

Between 0.022 inches and 0.055 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Mk15mod11t14

Insulation Resistance At Maximum Operating Temp:

100.0 megohm-microfarads

Capacitance Value Per Section:

1500.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

2.500

Terminal Surface Treatment:

Palladium and silver

Precious Material And Location:

Terminals surfaces palladium and terminals surfaces silver

Test Data Document:

81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 bonding pad

Specification Data:

81349-mil-c-55681/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0