NSN 5910-01-392-0893

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-392-0893 |
|---|
| Body Style: |
| W/o mtg facilities, terminal (s) on one end |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.500 inches |
| Body Diameter: |
| 0.187 inches |
| Body Length: |
| 0.468 inches |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| 0.140 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 10.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 105.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.190 |
| Equivalent Series Resistance At Reference Tempurature In Ohms: |
| 16.600 |
| Dc Leakage At Reference Temp: |
| 2.000 microamperes |
| Reference Tempurature At Which Rated: |
| 20.0 degrees celsius |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |

N/a

Shelf Life:

NSN 5910-01-392-0893

Electrolytic Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0