NSN 5910-01-392-1983

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-392-1983 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.100 **Terminal Length:** 1.500 inches **Body Diameter:** 0.289 inches **Body Length:** 0.686 inches **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 39.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Capacitive Electrode Material: Tantalum Test Data Document:** 81349-mil-c-39003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead **Specification Data:** 81349-mil-c-39003/6 government specification Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

Fiig: A010b0