

View Online at https://aerobasegroup.com/nsn/5910-01-392-3567

## **Body Style:** Rotary **Terminal Length:** Between 0.070 inches and 0.100 inches **Body Diameter:** Between 0.170 inches and 0.190 inches **Body Height:** Between 0.070 inches and 0.100 inches Center To Center Distance Between Terminals Parallel To Diameter: 0.140 inches **Terminal Width:** Between 0.018 inches and 0.022 inches **Terminal Thickness:** Between 0.003 inches and 0.005 inches **Inclosure Type:** Encased **Adjustment Device Torque:** Between 0.050 inch-ounces and 1.000 inch-ounces Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius **Capacitance Range In Picofarads:** +5.0/+15.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 square hole **Test Data Document:** 81349-mil-c-81 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 printed circuit **Specification Data:** 81349-mil-c-81/9 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig:

A096a0