NSN 5910-01-392-6292

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-392-6292

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

1.250 inches

Body Length:

Between 0.460 inches and 0.500 inches

Body Width:

Between 0.130 inches and 0.150 inches

Body Height:

Between 0.460 inches and 0.500 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.380 inches and 0.420 inches

Terminal Diameter:

Between 0.024 inches and 0.029 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

39000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Ceramic

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-20h government specification and 81349-mil-c-20/37d government specification

Shelf Life:

N/a

NSN 5910-01-392-6292

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0