## NSN 5910-01-392-6293

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-392-6293

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.001

**Terminal Length:** 

1.250 inches

**Body Length:** 

Between 0.460 inches and 0.500 inches

**Body Width:** 

Between 0.130 inches and 0.150 inches

**Body Height:** 

Between 0.460 inches and 0.500 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 0.280 inches and 0.420 inches

**Terminal Diameter:** 

Between 0.024 inches and 0.029 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

56000.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:** 

50.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-30.0/+30.0 single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

Case Material:

Ceramic

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

**Specification Data:** 

81349-mil-c-20/37d government specification

Shelf Life:

N/a

## NSN 5910-01-392-6293

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A010b0