NSN 5910-01-392-6363

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-392-6363

| Body Style: |
|---|
| W/o mtg facilities, terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Body Length: |
| 2.160 inches |
| Body Width: |
| 1.310 inches |
| Body Height: |
| 3.120 inches |
| Continuous Current Rating In Amps: |
| 7.0 |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.810 inches |
| Terminal Diameter: |
| 0.250 inches |
| Terminal Height From Body: |
| 1.250 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Internal Electrical Connection Type: |
| Extended foil |
| Capacitance Value Per Section: |
| 1.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 80.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 700.0 ac-rms single section |
| Criticality Code Justification: |
| Zzzy |
| Tolerance Range Per Section: |
| -10.00 to 10.00 percent single section |
| Case Material: |
| Metal |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.200 |
| Case Insulation Material: |
| Plastic |
| Special Features: |
| Item must comply with requirements of defense supply center colubmus production standard no. Lo4507 |
| Terminal Type And Quantity: |

2 standoff, threaded stud

NSN 5910-01-392-6363

Paper Dielectric Fixed Capacitor - Page 2 of 2



Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp.

| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A010b0