NSN 5910-01-393-1993

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-393-1993 **Body Style:** Chip type **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.001 **Terminal Length:** Between 0.005 inches and 0.015 inches **Body Length:** Between 0.090 inches and 0.145 inches **Body Width:** Between 0.090 inches and 0.130 inches **Body Height:** Between 0.030 inches and 0.102 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 1000.000 megohms **Capacitance Value Per Section:** 12.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -20.0/+20.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Ceramic **Insulation Resistance At Reference Temp:** 100000.0 megohms **Terminal Type And Quantity:** 2 bonding pad Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5910-01-393-1993

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0