# NSN 5910-01-393-2024

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-393-2024

## **Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.281 inches

**Body Diameter:** 

Between 1.743 inches and 1.805 inches

#### **Body Length:**

Between 4.093 inches and 4.217 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.644 inches and 0.766 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Diameter:

Between 0.644 inches and 0.766 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Electrical Polarization:**

Polarized

#### Mounting Facility Type And Quantity:

2 threaded mounting holes

## Capacitance Value Per Section:

2300.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

### **Thread Size:**

0.190 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

#### Case Material:

Metal

# Capacitive Electrode Material:

Aluminum

# Equivalent Series Resistance At Reference Tempurature In Ohms:

0.071

# Dc Leakage At Reference Temp:

1860.000 microamperes

# **Reference Tempurature At Which Rated:**

25.0 degrees celsius

# **Case Insulation Material:**

Plastic

Electrolytic Fixed Capacitor - Page 2 of 2



# Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0