NSN 5910-01-395-4944

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-395-4944

Body	Stv	le٠
Bouv	JLV	ıc.

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Length:

0.320 inches

Body Width:

0.200 inches

Body Height:

0.220 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.245 inches and 0.305 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

An/alq-135 iv

Insulation Resistance At Maximum Operating Temp:

100000.0 megohms

Capacitance Value Per Section:

10000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

0.100

Terminal Surface Treatment:

Solder

NSN 5910-01-395-4944

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Test Data Document:

81349-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Termin	al Type	And (Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-49467 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0