NSN 5910-01-395-7611

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-395-7611

$\mathbf{R} \mathbf{a} \mathbf{d}$	w	Sty	٠ما
DOU	ı y	OLY	C.

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Length:

0.570 inches

Body Width:

0.500 inches

Body Height:

. .

0.270 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.445 inches and 0.505 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

0.010 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.100

Reference Tempurature At Which Rated:

25.0 degrees celsius

Terminal Surface Treatment:

Solder

NSN 5910-01-395-7611

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0