

View Online at <https://aerobasegroup.com/nsn/5910-01-395-8700>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Not established

**Terminal Length:**

4.500 millimeters

**Body Diameter:**

16.500 millimeters

**Body Length:**

26.500 millimeters

**Center To Center Distance Between Terminals Parallel To Length:**

7.500 millimeters

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**End Application:**

Forrestal class cv; los angeles class ssn (688); ticonderoga class cg (47); emory s.Land class as; austin ship class lpd-4 amphibious transport docks; wasp class lhd; nimitz class cvn; oliver perry class ffg; arleigh burke class ddg; spruance class dd (963)

**Capacitance Value Per Section:**

102.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0