

View Online at <https://aerobasegroup.com/nsn/5910-01-395-8702>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

4.500 millimeters

Body Diameter:

16.500 millimeters

Body Length:

26.500 millimeters

Center To Center Distance Between Terminals Parallel To Length:

7.500 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

End Application:

Los angeles class ss (688); nimitz class cvn; ticonderoga class cg (47); wasp class lhd; oliver perry class ffg; forrestal class cv; spruance class dd (963) ; emory s. Land class as; arleigh burke class ddg; austin ship class lpd-4 amphibious transport docks

Capacitance Value Per Section:

222.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0