

View Online at https://aerobasegroup.com/nsn/5910-01-396-4583

Body Style:	
Dual inline	
Reliability Indicator:	
Established	
Reliability Failure Rate Le	vel In Percent:
0.0100	
Terminal Length:	
0.148 inches	
Body Length:	
0.092 inches	
Body Width:	
0.260 inches	
Body Height:	
0.128 inches	
Center To Center Distance	e Between Terminals Parallel To Width:
0.325 inches	
Schematic Diagram Desig	nator:
No common or grounded ele	ectrode (s)
Capacitance Value Per Se	ction:
10000.000 picofarads single	esection
Nonderated Operating Ter	np:
Between -55.0 degrees cels	ius and 125.0 degrees celsius
Cempurature Coefficient C	Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section	
Nonderated Continuous V	oltage Rating And Type Per Section:
50.0 dc single section	
Colerance Of Tempurature	e Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section	
Folerance Range Per Sect	ion:
5.00/+5.00 percent single s	ection
Case Material:	
Plastic	
Insulation Resistance At F	Reference Temp:
100000.0 megohms	
Dissipation Factor At Refe	erence Tempurature In Percent:
0.1500	
Test Data Document:	
81349-mil-c-39014 specifica	ation (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commerci	al catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performa	ance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quant	ity:
2 printed circuit	
Specification Data:	



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0