NSN 5910-01-397-6279

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-397-6279

Body Style:
N/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
1.625 inches
Body Diameter:
Between 0.531 inches and 0.593 inches
Body Length:
Between 1.063 inches and 1.187 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.150 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 dc single section
Tolerance Range Per Section:
10.00/+10.00 percent single section
Case Material:
Plastic
Test Data Document:
31349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Ferminal Type And Quantity:
2 uninsulated wire lead
Specification Data:
31349-mil-c-39022/01 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
A010b0