NSN 5910-01-399-2266

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-399-2266

Body Style:					
W/o mtg facilities terminal (s) on one surface					
Reliability Indicator:					
Not established					
Terminal Length:					
4.0 millimeters					
Body Length:					
13.0 millimeters					
Body Width:					
9.0 millimeters					
Body Height:					
4.0 millimeters					
Center To Center Distance Between Terminals Parallel To Length:					
10.0 millimeters					
Terminal Diameter:					
0.8 millimeters					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Capacitance Value Per Section:					
1.000 microfarads single section					
Nonderated Operating Temp:					
Between -55.0 degrees celsius and 85.0 degrees celsius					
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:					
400.0 single section					
Nonderated Continuous Voltage Rating And Type Per Section:					
100.0 dc single section					
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:					
-200.0/+200.0 single section					
Tolerance Range Per Section:					
-10.00/+10.00 percent single section					
Case Material:					
Plastic					
Terminal Surface Treatment:					
Solder					
Dielectric Material:					
Plastic polyester					
Terminal Type And Quantity:					
2 uninsulated wire lead					
Shelf Life:					
N/a					
Unit Of Measure:					

--

NSN 5910-01-399-2266

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Dem	ili	tar	izat	tic	n

No

Fiig:

A010b0